

Delivery program

OVER 100,000 TONS IN STOCK

1



Stock dimensions | Length: 6,000 - 16,000 mm | Width: 2,000 - 2,500 - 3,000 - 3,250 - 3,500 mm.

Quality designation Certificate Steel number Thickness

Unalloyed structural steel (EN 10025-2)

S235 JR+N / AR	3.1	1.0038	4 - 200 mm
S355 J2+N	3.1/3.2	1.0570	4 - 300 mm
S355 K2+N	3.2	1.0595	5 - 150 mm
S355 K2+N + NORSOK M120/MDS-Y05	3.2		6 - 80 mm
S355 K2+N + NORSOK M120/MDS-Y05/Z35 + US (S1/E2)	3.2		15 - 150mm

Unalloyed structural steel (EN 10025-2)

S355 N / NL	3.2	1.0545 / 1.0546	5 - 250 mm
S460 N / NL	3.1	1.8901 / 1.8903	8 - 150 mm
S460 NL / Z35 + US (S3/E4)	3.2		80 - 160 mm

Thermomechanically rolled fine grain structural steel plates (EN 10025-4)

S355 ML	3.2	1.8834	8 - 120 mm
S460 ML	3.2	1.8838	10 - 100 mm

High yield strength structural steel plates (EN 10025-6)

DILLIMAX® 690 T	S690QL	3.2	1.8928	6 - 250 mm
DILLIMAX® 690 E	S690QL1	3.2	1.8988	6 - 250 mm
DILLIMAX® 690 E	S690QL1 Z35 + US (S3/E4)	3.2		15 - 200 mm
DILLIMAX® 890 T	S890QL	3.1	1.8983	6 - 120 mm
DILLIMAX® 965 T	S960QL	3.1	1.8933	6 - 120 mm
DILLIMAX® 1100		3.1	1.8942	6 - 40 mm

Fine grain pressure vessel steel plates acc. to ASME standards

Unalloyed				
ASME SA 516 grade 60		3.1		3 - 200 mm
ASME SA 516 grade 70		3.2		5 - 250 mm
Alloyed				
ASME SA 387 Gr. 11 Cl. 2		3.1		6 - 60 mm
ASME SA 387 Gr. 12 Cl. 2		3.1		2 - 80 mm
ASME SA 387 Gr. 22 Cl. 2		3.1		6 - 50 mm

Steel plates for HIC-resistant pressure vessel construction acc. to ASME

DICREST®5 (HIC-resistant) volgens ASME SA 516 grade 60/65/70				10 - 120 mm
--	--	--	--	-------------

Fine grain pressure vessel steel plates, normalised (EN 10028-3)

P275 NH		3.1	1.0487	6 - 200 mm
P355 NH		3.2	1.0565	6 - 250 mm
P355 NL2		3.2	1.1106	6 - 250 mm
P460 NH		3.2	1.8935	8 - 150 mm
P460 NL2		3.2	1.8918	8 - 150 mm

DILLINGER

AncoferWaldram Steelplates bv is a company of Dillinger



